

Model : DCW08B-15 8W
 V1:+15V / 52~267mA
 V2:-15V / 52~267mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OUTPUT VOLTAGE ACCURACY	V1 : -2%~+2% (Max.) V2 : -2%~+2% (Max.)	I/P: 24VDC O/P:50% LOAD Ta:25°C	V1 : -0.04% V2 : -0.11%	P
2	RIPPLE & NOISE	V1 : 60mVp-p (Max.) V2 : 60mVp-p (Max.)	I/P:24VDC O/P:FULL LOAD Ta:25°C	V1 : 26mVp-p V2 : 28mVp-p	P
3	LINE REGULATION	V1 : -0.5%~+0.5% (Max.) V2 : -0.5%~+0.5% (Max.)	I/P:18VDC ~36VDC O/P:FULL LOAD Ta:25°C	V1 : -0%~+0% V2 : -0%~+0%	P
4	LOAD REGULATION	V1 : -0.5%~+0.5% (Max.) V2 : -0.5%~+0.5% (Max.)	I/P:24VDC O/P: MIN ~FULL LOAD Ta:25°C	V1 : -0.01%~+0.01% V2 : -0.01%~+0%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	16.1VDC~36VDC	P
2	EFFICIENCY	80% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	88.26%	P
3	INPUT CURRENT	426mA / FULL LOAD (Max.) 25mA / NO LOAD (Max.)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	380mA / FULL LOAD 11mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~250% (Typ)	I/P:24VDC O/P:TESTING Ta:25°C	220% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:SHORT Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT							
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P: FULL LOAD Ta= 25°C 2. HI AMBIENT BURN-IN : 3HRS I/P:24VDC O/P: FULL LOAD Ta= 60°C			P							
		<table border="1"> <thead> <tr> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>CASE</td> <td>CENTER</td> <td>45.4°C</td> <td>75.1°C</td> </tr> </tbody> </table>	Position	P/N		1	2	CASE	CENTER	45.4°C	75.1°C	
Position	P/N	1	2									
CASE	CENTER	45.4°C	75.1°C									
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:24VDC O/P:FULL LOAD Ta= -25°C	TEST : OK	P							
3	HIGH TEMPERATURE BURN IN TEST	NO DAMAGE	I/P:24VDC O/P:FULL LOAD Ta= 60°C	TEST : OK	P							

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1.5K VDC/min	I/P-O/P:1.5K VDC/ 1 min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2022.3.12	2212R	PASS	PETER	VINCENT ZENG