



Test Report : DETN01L-05N

1W SMD Package DC-DC Unregulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-5.0% ~ +5.0 %	I/P:5VDC O/P:FULL LOAD Ta:25°C	-2.22% -2.72%	P
2	RIPPLE & NOISE	100 mVp-p	I/P:5VDC O/P:FULL LOAD Ta:25°C	35 mV 33 mV	P
3	LINE REGULATION	-12% ~ +12%	I/P:4.5VDC~5.5VDC O/P:FULL LOAD Ta:25°C	-11.73% ~ +11.87% -11.80% ~ +11.91%	P
4	LOAD REGULATION	-8% ~ +8%	I/P:5VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-4.20% ~ +4.31% -4.39% ~ +4.46%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	78% (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25°C	78.28%	P
2	DC CURRENT	260 mA / FULL LOAD) 30 mA / NO LOAD	I/P:5VDC O/P:NO / FULL LOAD Ta:25°C	246.9 mA / FULL LOAD 26.3 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	5 second max	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	OK	P

SAFETY TEST
SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:3K VDC/min	I/P-O/P:3K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>10GΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>10GΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT												
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:5VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:5VDC O/P:FULL LOAD Ta=90°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:5VDC O/P:60% LOAD Ta=95°C			P												
<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>36.3°C</td> <td>99.6°C</td> <td>101.7°C</td> </tr> </tbody> </table>						NO	Position	P/N	1	2	3	1	CASE	CENTER	36.3°C	99.6°C	101.7°C
NO	Position	P/N	1	2	3												
1	CASE	CENTER	36.3°C	99.6°C	101.7°C												
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:5VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P												

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.95693 M.T.B.F : 1045 KHRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG