



# Test Report : DKMW30F-15

---

30W 1"x1" Package DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	V1 -0.28 % V2 -0.36 %	P
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	V1 64 mV V2 67 mV	P
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:9VDC-36VDC O/P:FULL LOAD Ta:25°C	V1 -0.011% ~ -0.005% V2 -0.007% ~ +0.001%	P
4	LOAD REGULATION	-1% ~ +1% (Max)	I/P:24VDC O/P:NO LOAD-FULL LOAD Ta:25°C	V1 -0.01 % ~ +0.01 % V2 -0.01 % ~ +0.01 %	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	88 % (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	88.6 %	P
2	DC CURRENT	1425 mA / FULL LOAD (Max) 10 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	1406 mA / FULL LOAD 10 mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~170% LOAD (Typ)	I/P:24VDC O/P:TESTING Ta:25°C	143.5 %	P
2	INPUT UNDER VOLTAGE LOCKOUT	Power Up 8.8V (Typ) Power Down 8.0V (Typ)	I/P:TESTING O/P: 10% LOAD Ta:25°C	Vin turn off : 8.01V Vin turn on : 8.44V	P
3	SHORT PROTECTION	CONTINUOUS	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE OK	P

**CONTROL FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >3.5Vdc~75Vdc or open Power off : R.C <1.2Vdc or short	I/P:24VDC O/P:10% LOAD Ta:25°C	OK	P

## SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

## RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 12HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 12HRS I/P:24VDC O/P:FULL LOAD Ta=61°C	<table border="1" data-bbox="651 1146 1147 1243"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>42.6°C</td> <td>76.4°C</td> </tr> </tbody> </table>	NO	Position	1	2	1	CASE	42.6°C	76.4°C		P
NO	Position	1	2										
1	CASE	42.6°C	76.4°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

### OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C,Full Load TOTAL FAILURE RATE : 0.819 M.T.B.F : 1,221,493 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ALROY WANG	VINCNET ZENG