

Model : DLW05C-12 5W DC-DC Dual Output Converter
 V1 : +12V / 20.8~208mA
 V2 : - 12V / 20.8~208mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	V1:-2%~+2% (Max) V2:-2%~+2% (Max)	I/P:48VDC O/P:50% LOAD Ta:25°C	V1:+0.5% V2:+0.8%	P
2	RIPPLE & NOISE	V1:100mVp-p (Max) V2:100mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1:15mV V2:18mV	P
3	LINE REGULATION	V1:-0.2%~+0.2% (Max) V2:-0.2%~+0.2% (Max)	I/P:36VDC~72VDC O/P:FULL LOAD Ta:25°C	V1:-0%~+0% V2:-0%~+0%	P
4	LOAD REGULATION	V1:-0.5%~+0.5% (Max) V2:-0.5%~+0.5% (Max)	I/P:48VDC O/P:MIN~FULL LOAD Ta:25°C	V1:-0%~+0.1% V2:-0%~+0%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	DC VOLTAGE RANGE	36VDC~72VDC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	16.2V~72V	P
2	EFFICIENCY	83% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	81.3%	P
3	DC CURRENT	135mA (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	128mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	YES	I/P:48VDC O/P:TESTING Ta:25°C	195% Hiccup Mode Reset Auto Recovery	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:48VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode Reset Auto Recovery	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT	
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 5HRS I/P:48VDC O/P:FULL LOAD Ta=25°C			P	
			Position	P/N		TEMP Ta=25°C
			CASE	DLW05C-12		35.1°C

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1KVDC/min	I/P-O/P:1KVDC/min Ta:25°C	I/P-O/P:0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:30GΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2003.8.28	DLW05C-12	PASS	FRANK.CHEN	MAX LIN