



Test Report : DPBW06G-12

6W SIP Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1 -0.36 % V2 -0.33 %	P
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1 80 mV V2 92 mV	P
3	LINE REGULATION	-0.2% ~ +0.2% (Max)	I/P:18VDC~75VDC O/P:FULL LOAD Ta:25°C	V1 -0.001% ~ +0.008% V2 -0.001% ~ +0.017%	P
4	LOAD REGULATION	-1% ~ +1% (Max)	I/P:48VDC O/P:NO LOAD-FULL LOAD Ta:25°C	V1 -0.15 % ~ +0.15 % V2 -0.16 % ~ +0.16 %	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	89 % (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	90.2 %	P
2	DC CURRENT	145 mA / FULL LOAD (Max) 3 mA / NO LOAD (Max)	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	135 mA / FULL LOAD 3 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	YES	I/P:48VDC O/P:TESTING Ta:25°C	154 %	P
2	SHORT PROTECTION	CONTINUOUS	I/P:75VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE OK	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C = High Impedance or open Power off : R.C = 2~4mA	I/P:48VDC O/P:10% LOAD Ta:25°C	PASS	P

SAFETY TEST
SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 12HRS I/P:48VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 12HRS I/P:48VDC O/P:FULL LOAD Ta=61°C			P								
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>42.4°C</td> <td>74.6°C</td> </tr> </tbody> </table>		NO	Position	1	2	1	CASE	42.4°C	74.6°C		
NO	Position	1	2										
1	CASE	42.4°C	74.6°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:48VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	M MIL-HDBK-217F,GB, 25°C, Full Load TOTAL FAILURE RATE : 0.592 M.T.B.F : 2,017,455 HRS 1,689,621			P

TEST RESULT	TESTER	APPROVAL
PASS	ALROY WANG	VINCENT ZENG