



Test Report: NLDD-1050H

DC-DC Constant Current Step-Down LED driver

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST



NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CURRENT ACCURACY	-5%~+5%	I/P: 48VDC O/P: LED max/ LED min Ta:25°C	-1.33%~3.43%/48DC
2	CURRENT RIPPLE	-5%~+5%	I/P: 48VDC O/P: LED min~ LED max Ta:25°C	2.57%~ 1.87%/48DC
3	SUGRE CURRENT	< +10%	I/P: 48VDC O/P: LED max/ LED min Ta:25°C	9.71%~ 9.71%/48 VDC
4	VOLTAGE RANGE	6~52 VDC	I/P: 10- 56VDC O/P:TEST Ta:25°C	6-52 VDC

5	DIMMING OPERATION	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <h4 style="background-color: #cccccc; padding: 2px;">PWM Dimming Control</h4> </div> <div style="width: 45%;"> <ul style="list-style-type: none"> ⊙ Short circuit PWM PIN can realize dimming turn off. ⊙ During PWM dimming operation, the output current will change to PWM style. </div> </div>																																								
		<p>I/P : 48 VDC O/P : DIMMING TEST</p> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>PWM</th> <th>0%</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> <th>OPEN</th> </tr> </thead> <tbody> <tr> <td>Output Current (100Hz)</td> <td>0</td> <td>0.103</td> <td>0.208</td> <td>0.311</td> <td>0.420</td> <td>0.525</td> <td>0.627</td> <td>0.725</td> <td>0.828</td> <td>0.931</td> <td>1.035</td> <td>1.040</td> </tr> <tr> <td>%</td> <td>0</td> <td>9.52</td> <td>19.819.81</td> <td>29.62</td> <td>40.0</td> <td>50.0</td> <td>59.71</td> <td>69.05</td> <td>78.86</td> <td>88.67</td> <td>98.57</td> <td>99.05</td> </tr> </tbody> </table>		PWM	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN	Output Current (100Hz)	0	0.103	0.208	0.311	0.420	0.525	0.627	0.725	0.828	0.931	1.035	1.040	%	0	9.52	19.819.81	29.62	40.0	50.0	59.71	69.05	78.86	88.67	98.57	99.05
		PWM	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN																												
Output Current (100Hz)	0	0.103	0.208	0.311	0.420	0.525	0.627	0.725	0.828	0.931	1.035	1.040																														
%	0	9.52	19.819.81	29.62	40.0	50.0	59.71	69.05	78.86	88.67	98.57	99.05																														
<p>TEST RESULT : OK</p>																																										

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	10VDC~ 56VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	9.8 ~ 59 VDC
			I/P: LOW-LINE-0.2 VDC = 9.8 VDC HIGH-LINE+3 VDC = 59 VDC O/P:FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	TEST(1) <u>OK</u> (2) <u>OK</u> (3) <u>OK</u>
2	INPUT CURRENT(TYP)	1100mA @48VDC*FULL LOAD 5mA @48VDC*NO LOAD	I/P:48 VDC O/P:FULL LOAD/NO LOAD Ta:25°C	I =976mA/VDC(FULL LOAD) I =1.52mA/VDC(NO LOAD)
3	EFFICIENCY(TYP)	96%	I/P: 36/48VDC O/P:FULL LOAD Ta:25°C	96.69%/48 VDC 96.03%/36 VDC

EFFICIENCY vs LOAD



PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P: 48VDC O/P:FULL LOAD	PROTECTION TYPE : Shut down, recovers Automatically after temperature goes down
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 10VDC/48VDC/56VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE OK PROTECTION TYPE : Can be continued , recovers automatically after fault condition is removed

CONTROL FUNCTION TEST

1	REMOTE CONTROL	1. Power ON with dimming: DIM ~ -Vin >2.5 ~ 6VDC or open circuit 2. Power OFF : DIM ~ -Vin < 0.8VDC or short	I/P: 10VDC/24 VDC /5 VDC O/P:FULL LOAD	IP:10DC 1、 Power OFF: <1.77VDC Power ON: >1.91VDC IP:24DC 2、 Power OFF: <1.77VDC Power ON: >1.90 VDC IP:59DC 3、 Power OFF: <1.77VDC Power ON: >1.94VDC
2	QUIESCENT INPUT CURRENT IN SHUTDOWN MODE(max.)	2mA at PWM dimming OFF and 24VDC input	I/P: 24 VDC O/P:FULL LOAD	1.29mA

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	U1 Rated MBI6662 2A/ 75V	DC ON/OFF I/P:High-Line +3 VDC =59 VDC VDS: O/P: (1) CV max (2) CV max continue (3) CV min (4)Output Short (5)NO LOAD (6)DIM off I/P:Low-Line -0.2 VDC =9.8 VDC O/P: (1) CV max (2) CV max continue (3) CV min (4)Output Short (5)NO LOAD (6)DIM off Ta:25°C	VDS: 59V (1) 61.2V (2) 60.4V (3) 60.8V (4) 60.8V (5) 60.4V (6) 59.6V VDS: 9.8V (1) 11.52V (2) 11.36V (3) 11.44V (4) 11.44V (5) 10.63V (6) 10.47V

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RADIATION	EN55015 CLASS A	I/P: 56VDC O/P:FULL LOAD Ta:25°C	PASS
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P: 56VDC O/P:FULL LOAD Ta:25°C	CRITERIA A
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 0.5KV	I/P: 56VDC O/P:FULL LOAD Ta:25°C	CRITERIA A
4	Test by certified Lab & Test Report Prepare Any contradictions of the test results, please refer to the latest EMC test report			

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																								
1	TEMPERATURE RISE TEST	MODEL : NLDD-1050HW 1. ROOM AMBIENT BURN-IN : 2HRS I/P : 48VDC O/P : FULL LOAD Ta= 28.4°C 2. HIGH AMBIENT BURN-IN : HRS I/P : 56VDC O/P : FULL LOAD Ta= 51.7 °C																										
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta=28.4 °C</th> <th>HIGH AMBIENT Ta=51.7 °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U1</td> <td>47.3°C</td> <td>80.9°C</td> </tr> <tr> <td>2</td> <td>C1</td> <td>42.4°C</td> <td>69.9°C</td> </tr> <tr> <td>3</td> <td>D2</td> <td>45.7°C</td> <td>73.0°C</td> </tr> <tr> <td>4</td> <td>L1</td> <td>46.1°C</td> <td>74.2°C</td> </tr> <tr> <td>5</td> <td>TC</td> <td>39.2°C</td> <td>69.5°C</td> </tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta=28.4 °C	HIGH AMBIENT Ta=51.7 °C	1	U1	47.3°C	80.9°C	2	C1	42.4°C	69.9°C	3	D2	45.7°C	73.0°C	4	L1	46.1°C	74.2°C	5	TC	39.2°C	69.5°C
NO	Position	ROOM AMBIENT Ta=28.4 °C	HIGH AMBIENT Ta=51.7 °C																									
1	U1	47.3°C	80.9°C																									
2	C1	42.4°C	69.9°C																									
3	D2	45.7°C	73.0°C																									
4	L1	46.1°C	74.2°C																									
5	TC	39.2°C	69.5°C																									
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 10VDC / 56VDC O/P : FULL LOAD Ta= -45 °C	TEST : OK																								
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C/95 %R.H NO DAMAGE	I/P : 56VDC O/P : FULL LOAD Ta= 55°C HUMIDITY= 95 %R.H	TEST : OK																								
4	TEMPERATURE COEFFICIENT	+ 0.03%/°C(0~50°C)	I/P : 56VDC O/P : FULL LOAD	+ 0.001 %/°C(0~50°C)																								

6	STORAGE TEMPERATURE TEST	-40~85°C	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : STATIC
7	THERMAL SHOCK TEST	-40~50°C	1. Thermal shock Temperature : -45°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 15cycle: 56VDC / FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle: 56VDC / FULL LOAD Burn In Test
8	VIBRATION TEST	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 3G (5) Test Time : 180min in each axis (X.Y.Z) (6) Ta : 25°C
9	CAPACITOR LIFE CYCLE	SUPPOSE C1 IS THE MOST CRITICAL COMPONENT (1) I/P : 48VDC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 56VDC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 56VDC O/P : 75% LOAD Ta=50 °C LIFE TIME (4) I/P : 56VDC O/P : 50% LOAD Ta=50 °C LIFE TIME	(1) 729024HRS (2) 131582HRS (3) 70911HRS (4) 59044HRS
10	MTBF	Conducted by Parts Stress Analysis Prediction 29984.3K hrs min. Telcordia SR-332 (Bellcore); 2881.6K hrs min. MIL-HDBK-217F (25°C)	
11	Ongoing Reliability Test	I/P : 56VDC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 30,000 hours	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	WUWQ/HUANGMK	WENF	LINKX