



MODEL : NSD05-48S12

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 75 mVp-p (Max)	I/P: 48VDC O/P:FULL LOAD Ta:25°C	V1: 16 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 %- -2 % (Max)	I/P: 18VDC / 72VDC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.05 %~ -0.05 %	P
3	LINE REGULATION	V1: 1%~ -1 % (Max)	I/P: 18VDC ~ 72VDC O/P:FULL LOAD Ta:25°C	V1: 0 %~ 0 %	P
4	LOAD REGULATION	V1: 1 %- -1 % (Max)	I/P: 48VDC O/P:FULL -MIN LOAD Ta:25°C	V1: 0.05 %~ -0.05 %	P
6	OVER/UNDERSHOOT TEST	< ±5%	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
7	DYNAMIC LOAD	V1: 1200 mVp-p	I/P: 48VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	165 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~ 72 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	6.6 V~ 72 V	P
			I/P: LOW-LINE-0.2V= 17.8 V HIGH-LINE+5%= 75.6 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	83 % (TYP)	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	83.7 %	P
3	INPUT CURRENT	48 VDC/ 0.2A(TYP)	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	I = 0.124 A	P
4	SHUTDOWN IDLE CURRENT	5 mA / 48VDC	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	3.7 mA / 48VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 48VDC O/P: TESTING Ta:25°C	235% / 48V Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 13.5 V~ 16.5V	I/P: DC SOURCE O/P: MIN LOAD Ta:25°C	15.1V / 0.047A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1hour NO DAMAGE	I/P: 72 VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE Hiccup	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 48VDC O/P: FULL LOAD Ta:25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	MODEL : NSD05-48S12 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 48VDC O/P: FULL LOAD Ta= 9°C 2. HIGH AMBIENT BURN-IN : 1 HRS I/P: 48 VDC O/P: FULL LOAD Ta= °C			P
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 48VDC O/P: 120 % LOAD Ta:25°C	TEST : OK	P
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 48 VDC O/P: 80 % LOAD Ta= -25 °C	TEST : OK	P
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60°C NO DAMAGE	I/P: 75 VDC O/P:FULL LOAD Ta= 60°C HUMIDITY= 95 %R.H	TEST : OK	P
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-60°C)	I/P: 48 VDC O/P:FULL LOAD	± 0.003 %(0-60°C)	P
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1KVDC/min	I/P-O/P: 1.2KVDC/min Ta:25°C	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C / 70% RH	I/P-O/P: 24 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO :			N/A



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 48VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
4	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 914.4K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q6 Rated IRFR-220N : 5A/200V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 112 V (2) 115 V	P
2	Diode Peak Voltage	D100 Rated 6CWQ10FN 7A/100V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 60 V (2) 45 V	P
3	Input Capacitor Voltage	C5 Rated : 224 / 100V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 75 V (2) 75 V (3) 75 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 30 V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 10.1 V (2) 8.41 V (3) 10.1 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/6/20	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/8/3	PRODUCT SAMPLE W0707B35	PASS	VINCENT TSENG	MAX LIN
2007/12/24	PRODUCT SAMPLE W0712B25	PASS	SANFORD SU	VINCENT TSENG

2003/12/12 A50-F023