



# Test Report: RSD-500B-24

---

500W Enclosed Type Reliable Railway DC-DC Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

ENVIRONMENT TEST

## DESIGN VERIFY TEST


### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE ADJUST RANGE	CH1: 24V~ 28V	I/P: 24VDC O/P : MIN LOAD Ta : 25°C	23.447V~29.447V
2	OUTPUT VOLTAGE TOLERANCE (Max)	V1: -1%~+1 %	I/P: 16.8VDC / 33.6 VDC O/P:FULL/ MIN. LOAD Ta:25°C	V1: -0.08%~0.03%
3	LINE REGULATION (Max)	V1: -0.5%~+0.5 %	I/P: 16.8 VDC / 33.6 VDC O/P:FULL LOAD Ta:25°C	V1: -0.02%~0.03%
4	LOAD REGULATION (Max)	V1: -1%~ +1 %	I/P: 24VDC O/P:FULL ~MIN LOAD Ta:25°C	V1: -0.08%~0.03%
5	OVER/UNDERSHOOT TEST	< ±5%	I/P: 24VDC O/P:FULL LOAD Ta:25°C	TEST:1.3%
6	RIPPLE & NOISE (Max)	V1: 120 mVp-p	I/P: 24VDC O/P:FULL LOAD Ta:25°C	V1: 20mVp-p

high frequency :




low frequency :







7	SET UP TIME (Max)	24VDC/ 500ms	I/P: 24VDC O/P:FULL LOAD Ta:25°C	110.2ms
---	-------------------	--------------	--	---------

INPUT= 24VDC @ FULL LOAD

CH1 : Output Voltage CH2 : DC Input Voltage




8	RISE TIME (Max)	24VDC / 60 ms	I/P: 24VDC O/P:FULL LOAD Ta:25°C	9.34ms
<p>INPUT=24 VDC @ FULL LOAD CH1 : Output Voltage</p> 				
9	HOLD UP TIME (TYP)	24VDC / 3 ms	I/P: 24VDC O/P:FULL LOAD Ta:25°C	10.8ms
<p>INPUT=24 VDC @ FULL LOAD CH1 : Output Voltage CH2 : DC Input Voltage</p> 				
10	TRANSIENT RECOVERY TIME	V1:2400mVp-p	I/P: 24VDC O/P:40% LOAD CHANGE 50%DUTY/120HZ	192mVp-p
11	DYNAMIC LOAD	V1: 2400mVp-p	I/P: 24VDC O/P: (1)FULL /50% LOAD 50%DUTY / 120HZ (2)FULL /50% LOAD 50%DUTY / 1KHZ Ta:25°C	245mVp-p 221mVp-p
<p>FULL /50% LOAD 50%DUTY / 120HZ</p>  <p>FULL /50% LOAD 50%DUTY / 1KHZ</p> 				

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	16.8VDC~ 33.6VDC 14.4 VDC~16.8VDC/1s	I/P:TESTING O/P:FULL LOAD Ta:25°C	(1) 15.89V~ 33.6V (2) TEST:OK
			I/P: LOW-LINE-0.2= 16.6V HIGH-LINE+1V= 34.6V O/P:FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN ( POWER ON/OFF NO DAMAGE )	TEST:OK
2	INPUT CURRENT(TYP)	24VDC/ 21.5 A	I/P: 24VDC O/P:FULL LOAD Ta:25°C	I=18.92A
3	EFFICIENCY(TYP)	92 %	I/P: 24VDC O/P:FULL LOAD Ta:25°C	92.93%


EFFICIENCY vs LOAD



4	INRUSH CURRENT(TYP)	30A COLD START	I/P: 24VDC O/P:FULL LOAD Ta:25°C	I=24.5A
---	---------------------	-------------------	--	---------

INPUT= VDC @ FULL LOAD

CH2 : DC Input Voltage CH4 : Input current



5	INTERRUPTION OF VOLTAGE SUPPLY	B- type comply with S2 level (10ms)@ 70% load ;	I/P: 24VDC SHORT O/P: TESTING Ta:25°C	16 ms/ 70% load
---	--------------------------------	--	---	-----------------



PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	Constant current limiting 105%~135% rated output power with auto-recovery.	I/P: 16.8 VDC I/P: 24 VDC I/P: 33.6 VDC O/P: TESTING Ta:25°C	121.1%/ 16.8 VDC 121.3%/ 24 VDC 121.2%/ 33.6 VDC PROTECTION TYPE : Constant current limiting 105%~135% rated output power with auto-recovery .
2	OVER VOLTAGE PROTECTION	CH: 28.8 V~ 35 V	I/P: 16.8 VDC I/P: 24 VDC I/P: 33.6 VDC O/P: MIN LOAD Ta:25°C	30.8V/ 16.8 VDC 30.8V/ 24 VDC 30.8V/ 33.6 VDC PROTECTION TYPE : Shut down O/P voltage, re-power on to recover
3	OVER TEMPERATURE PROTECTION	SPEC: NO DAMAGE	I/P: 33.6/16.8 VDC O/P: FULL LOAD	O.T.P. Active PROTECTION TYPE : Shut down O/P voltage, re-power on to recover
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 33.6/16.8 VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE PROTECTION TYPE : Constant current limiting with auto-recovery recovers automatically after fault condition is removed
5	INPUT REVERSE	POWER OK	I/P: 33.6/16.8 VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE
6	INPUT UNDER VOLTAGE PROTECTION	24 VIN (B-TYPE) : POWER ON >=16.8V POWER OFF <=16.5V	I/P: TESTING O/P: FULL LOAD Ta:25°C	TEST : POWER ON >= 15.886 V POWER OFF <= 13.965 V

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																				
1	PWM Transistor ( D to S) or (C to E) Peak Voltage	Q 10/Q12/ Q21/Q23 Rated : 100 A/ 100 V	DC ON/OFF  I/P: High-Line +1V =34.6V VDS: O/P: (1) Full Load (2) Output Short (3) Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4) Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5) Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6) Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7) 0%→400% Load. Ta:25°C	<table border="0"> <tr> <td><b>Q10</b></td> <td><b>Q12</b></td> </tr> <tr> <td>VDS:</td> <td>VDS:</td> </tr> <tr> <td>(1) 55.2V</td> <td>(1) 56.0V</td> </tr> <tr> <td>(2) 89.4V</td> <td>(2) 87.0V</td> </tr> <tr> <td>(3) 75.8V</td> <td>(3) 75.8V</td> </tr> <tr> <td>(4) 72.5V</td> <td>(4) 70.9V</td> </tr> <tr> <td>(5) 66.1V</td> <td>(5) 69.9V</td> </tr> <tr> <td>(6) 66.9V</td> <td>(6) 70.9V</td> </tr> <tr> <td>(7) 91.9V</td> <td>(7) 90.3V</td> </tr> <tr> <td><b>Q21</b></td> <td><b>Q23</b></td> </tr> <tr> <td>VDS:</td> <td>VDS:</td> </tr> <tr> <td>(1) 61.6V</td> <td>(1) 59.6V</td> </tr> <tr> <td>(2) 91.8V</td> <td>(2) 92.6V</td> </tr> <tr> <td>(3) 73.3V</td> <td>(3) 76.6V</td> </tr> <tr> <td>(4) 72.5V</td> <td>(4) 71.7V</td> </tr> <tr> <td>(5) 72.5V</td> <td>(5) 72.5V</td> </tr> <tr> <td>(6) 71.7V</td> <td>(6) 70.1V</td> </tr> <tr> <td>(7) 87.9V</td> <td>(7) 90.3V</td> </tr> </table>	<b>Q10</b>	<b>Q12</b>	VDS:	VDS:	(1) 55.2V	(1) 56.0V	(2) 89.4V	(2) 87.0V	(3) 75.8V	(3) 75.8V	(4) 72.5V	(4) 70.9V	(5) 66.1V	(5) 69.9V	(6) 66.9V	(6) 70.9V	(7) 91.9V	(7) 90.3V	<b>Q21</b>	<b>Q23</b>	VDS:	VDS:	(1) 61.6V	(1) 59.6V	(2) 91.8V	(2) 92.6V	(3) 73.3V	(3) 76.6V	(4) 72.5V	(4) 71.7V	(5) 72.5V	(5) 72.5V	(6) 71.7V	(6) 70.1V	(7) 87.9V	(7) 90.3V
<b>Q10</b>	<b>Q12</b>																																							
VDS:	VDS:																																							
(1) 55.2V	(1) 56.0V																																							
(2) 89.4V	(2) 87.0V																																							
(3) 75.8V	(3) 75.8V																																							
(4) 72.5V	(4) 70.9V																																							
(5) 66.1V	(5) 69.9V																																							
(6) 66.9V	(6) 70.9V																																							
(7) 91.9V	(7) 90.3V																																							
<b>Q21</b>	<b>Q23</b>																																							
VDS:	VDS:																																							
(1) 61.6V	(1) 59.6V																																							
(2) 91.8V	(2) 92.6V																																							
(3) 73.3V	(3) 76.6V																																							
(4) 72.5V	(4) 71.7V																																							
(5) 72.5V	(5) 72.5V																																							
(6) 71.7V	(6) 70.1V																																							
(7) 87.9V	(7) 90.3V																																							
2	Clamp MOSFET ( D to S) or (C to E) Peak Voltage	Q8/Q19 Rated : 73 A/ 100 V	DC ON/OFF	<table border="0"> <tr> <td><b>Q8</b></td> <td><b>Q19</b></td> </tr> <tr> <td>VDS:</td> <td>VDS:</td> </tr> </table>	<b>Q8</b>	<b>Q19</b>	VDS:	VDS:																																
<b>Q8</b>	<b>Q19</b>																																							
VDS:	VDS:																																							

		VGS $\pm$ 20 V	<p>I/P:High-Line +1V =34.6</p> <p>VDS:</p> <p>O/P: (1)Full Load          (2)Output Short          (3)Dynamic Load Full Load/          Min. Load 90%Duty/1KHz          (4)Dynamic Load Full Load/          Min. Load 90%Duty/3KHz          (5)Dynamic Load Full Load/          Min. Load 90%Duty/5KHz          (6)Dynamic Load 100% Load/          Min. Load 50%Duty/120Hz          (7)0%→400% Load.</p> <p>Ta:25°C</p>	<p>(1) 48.2V          (2) 78.5V          (3) 87.5V          (4) 60.6V          (5) 57.4V          (6) 72.2V          (7) 85.5V</p>	<p>(1) 47.1V          (2) 76.6V          (3) 71.7V          (4) 55.7V          (5) 56.5V          (6) 74.9V          (7) 81.4V</p>
3	Diode Peak Voltage	<p>Q100/ Q201 Rated          : 20A/200V</p> <p>Q103/Q105 Rated          : 65 A/200V</p>	<p>DC ON/OFF</p> <p>I/P:High-Line +1V =34.6 V</p> <p>VOmax:</p> <p>O/P: (1)Full Load          (2)Output Short          (3)Dynamic Load Full Load/          Min. Load 90%Duty/1KHz          (4)Dynamic Load Full Load/          Min. Load 90%Duty/3KHz          (5)Dynamic Load Full Load/          Min. Load 90%Duty/5KHz          (6)Dynamic Load 100% Load/          Min. Load 50%Duty/120Hz          (7)0%→400% Load.          (8).NO LOAD</p> <p>VO          O/P: (1)Full Load</p> <p>Ta:25°C</p>	<p>Q100:          VOmax:          VDS:          (1) 124.5V          (2) 163V          (3) 177V          (4) 167V          (5) 167V          (6) 165V          (7) 142V          (8) 86.8V          VO:          (1) 110.8V</p> <p>Q103:          VOmax:          VDS:          (1) 169V          (2) 163V          (3) 169V          (4) 173V          (5) 173V          (6) 169V          (7) 172V          (8) 171V          VO:          (1) 159V</p>	<p>Q200:          VOmax:          VDS:          (1) 110V          (2) 165V          (3) 175V          (4) 165V          (5) 167V          (6) 167V          (7) 110V          (8) 85.1V          VO:          (1) 95.6V</p> <p>Q105:          VOmax:          VDS:          (1) 167V          (2) 173V          (3) 171V          (4) 173V          (5) 171V          (6) 171V          (7) 174V          (8) 163V          VO:          (1)159V</p>
4	Input Capacitor Voltage	C5/C35 Rated: : 3300 $\mu$ / 35 V	<p>I/P:High-Line +1V =34.6</p> <p>O/P: (1)Full Load input on/off          (2) Min load input on /Off          (3)Full Load /Min load Change          (4)Full load continue</p> <p>Ta:25°C</p>	<p>C5          (1) 34.5V          (2) 34.1V          (3) 34.7V          (4) 34.3V</p>	<p>C35          (1) 34.7V          (2) 34.1V          (3) 34.7V          (4) 34.7V</p>
5	Control IC Voltage Test	<p>PWM IC U4 Rated          7.5V~ 15 V          O/P U100 /U101 Rated          -0.3V~ 27 V          O/P U201 Rated          0V~ 32 V</p>	<p>DC ON/OFF</p> <p>I/P:High-Line +1V =34.6 V</p> <p>O/P(1)FULL LOAD          (2) Output Short          (3)O.L.P          (4)O.V.P.          (5)NO LOAD VRmin(LOW LINE)</p>	<p>U4          (1) 14.14V          (2) 14.14V          (3) 14.14V          (4) 14.2V          (5) 11.49V</p> <p>U100          (1) 10.92V</p>	<p>U201          (1) 13.6V          (2) 13.6V          (3) 13.6V          (4) 19.9V          (5) 13.0V</p> <p>U101          (1) 10.12V</p>

			Ta:25°C	(2) 10.84V (3) 10.92V (4) 10.92V (5) 10.84V	(2) 10.12V (3) 10.04V (4) 10.12V (5) 10.04V
--	--	--	---------	--	--

**SAFETY TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	EN 60950-1 I/P-O/P:4KVDC/min I/P-FG:2.5 KVDC/min O/P-FG:2.5KVDC/min	I/P-O/P: 4.4KVDC/min I/P-FG: 3 KVDC/min O/P-FG:3KVDC/min Ta:25°C	I/P-O/P: 0.2 uA I/P-FG: 0.5 uA O/P-FG: 0 uA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 600 VDC I/P-FG: 600 VDC O/P-FG: 600 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG: 9999MΩ NO DAMAGE
3	GROUNDING CONTINUITY	EN 60950-1 FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40A / 2min Ta:25°C	2mΩ

**E.M.C TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RADIATION	EN55032 CLASS B	I/P: 24VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
2	CONDUCTION	EN55032 CLASS A	I/P: 24VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
3	E.S.D	EN61000-4-2 <input type="checkbox"/> MEDICAL AIR: 15KV / Contact: 8KV <input type="checkbox"/> LIGHT INDUSTRY AIR: 8KV / Contact: 4KV <input checked="" type="checkbox"/> INDUSTRY AIR: 8KV / Contact: 6KV	I/P: 24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
4	E.F.T	EN61000-4-4 <input type="checkbox"/> LIGHT INDUSTRY INPUT: 0.5KV <input type="checkbox"/> MEDICAL <input checked="" type="checkbox"/> INDUSTRY INPUT: 2KV	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
5	SURGE	IEC61000-4-5 <input checked="" type="checkbox"/> INDUSTRY L-N :1KV L,N-PE:2KV	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
6	Test by certified Lab & Test Report Prepare Any contradictions of the test results, please refer to the latest EMC test report			

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																																																																																																																								
1	TEMPERATURE RISE TEST	MODEL : RSD-500B-48 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 24 VDC O/P : FULL LOAD Ta= 25 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 24 VDC O/P : FULL LOAD Ta= 55 °C																																																																																																																																																																										
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 25 °C</th> <th>HIGH AMBIENT Ta= 55 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>66.6°C</td><td>96.4°C</td></tr> <tr><td>2</td><td>C17</td><td>69.7°C</td><td>98.9°C</td></tr> <tr><td>3</td><td>LF2</td><td>71.6°C</td><td>101.2°C</td></tr> <tr><td>4</td><td>Q1</td><td>66.0°C</td><td>95.4°C</td></tr> <tr><td>5</td><td>C6</td><td>68.9°C</td><td>98.4°C</td></tr> <tr><td>6</td><td>Q10</td><td>68.4°C</td><td>98.0°C</td></tr> <tr><td>7</td><td>ZNR1</td><td>61.8°C</td><td>91.2°C</td></tr> <tr><td>8</td><td>C14</td><td>67.4°C</td><td>96.5°C</td></tr> <tr><td>9</td><td>RY</td><td>67.6°C</td><td>96.6°C</td></tr> <tr><td>10</td><td>Q39</td><td>73.1°C</td><td>101.1°C</td></tr> <tr><td>11</td><td>R90</td><td>81.0°C</td><td>108.0°C</td></tr> <tr><td>12</td><td>D2</td><td>67.4°C</td><td>97.1°C</td></tr> <tr><td>13</td><td>Q23</td><td>69.5°C</td><td>99.7°C</td></tr> <tr><td>14</td><td>C18</td><td>68.2°C</td><td>97.7°C</td></tr> <tr><td>15</td><td>U2</td><td>70.5°C</td><td>99.9°C</td></tr> <tr><td>16</td><td>T3</td><td>72.6°C</td><td>103.0°C</td></tr> <tr><td>17</td><td>T5</td><td>71.5°C</td><td>101.5°C</td></tr> <tr><td>18</td><td>U4</td><td>76.7°C</td><td>106.6°C</td></tr> <tr><td>19</td><td>Q8</td><td>66.5°C</td><td>96.3°C</td></tr> <tr><td>20</td><td>TSW1</td><td>70.0°C</td><td>100.4°C</td></tr> <tr><td>21</td><td>T4</td><td>72.6°C</td><td>103.0°C</td></tr> <tr><td>22</td><td>Q19</td><td>65.6°C</td><td>96.0°C</td></tr> <tr><td>23</td><td>T6</td><td>71.6°C</td><td>102.1°C</td></tr> <tr><td>24</td><td>T2</td><td>73.9°C</td><td>104.4°C</td></tr> <tr><td>25</td><td>Q201</td><td>71.5°C</td><td>101.7°C</td></tr> <tr><td>26</td><td>Q104</td><td>70.1°C</td><td>100.1°C</td></tr> <tr><td>27</td><td>L101</td><td>75.8°C</td><td>107.6°C</td></tr> <tr><td>28</td><td>T1</td><td>71.1°C</td><td>101.6°C</td></tr> <tr><td>29</td><td>Q100</td><td>69.9°C</td><td>100.4°C</td></tr> <tr><td>30</td><td>Q103</td><td>70.7°C</td><td>100.9°C</td></tr> <tr><td>31</td><td>L100</td><td>73.5°C</td><td>105.4°C</td></tr> <tr><td>32</td><td>C115</td><td>68.1°C</td><td>99.2°C</td></tr> <tr><td>33</td><td>LF100</td><td>58.4°C</td><td>89.4°C</td></tr> <tr><td>34</td><td>C103</td><td>68.5°C</td><td>99.2°C</td></tr> <tr><td>35</td><td>C102</td><td>66.3°C</td><td>96.9°C</td></tr> <tr><td>36</td><td>U201</td><td>66.3°C</td><td>96.5°C</td></tr> <tr><td>37</td><td>U5</td><td>65.9°C</td><td>96.0°C</td></tr> <tr><td>38</td><td>Q204</td><td>65.8°C</td><td>95.8°C</td></tr> <tr><td>39</td><td>Q37</td><td>69.7°C</td><td>99.0°C</td></tr> <tr><td>40</td><td>U3</td><td>69.7°C</td><td>99.5°C</td></tr> <tr><td>41</td><td>Q17</td><td>69.4°C</td><td>100.0°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 25 °C	HIGH AMBIENT Ta= 55 °C	1	LF1	66.6°C	96.4°C	2	C17	69.7°C	98.9°C	3	LF2	71.6°C	101.2°C	4	Q1	66.0°C	95.4°C	5	C6	68.9°C	98.4°C	6	Q10	68.4°C	98.0°C	7	ZNR1	61.8°C	91.2°C	8	C14	67.4°C	96.5°C	9	RY	67.6°C	96.6°C	10	Q39	73.1°C	101.1°C	11	R90	81.0°C	108.0°C	12	D2	67.4°C	97.1°C	13	Q23	69.5°C	99.7°C	14	C18	68.2°C	97.7°C	15	U2	70.5°C	99.9°C	16	T3	72.6°C	103.0°C	17	T5	71.5°C	101.5°C	18	U4	76.7°C	106.6°C	19	Q8	66.5°C	96.3°C	20	TSW1	70.0°C	100.4°C	21	T4	72.6°C	103.0°C	22	Q19	65.6°C	96.0°C	23	T6	71.6°C	102.1°C	24	T2	73.9°C	104.4°C	25	Q201	71.5°C	101.7°C	26	Q104	70.1°C	100.1°C	27	L101	75.8°C	107.6°C	28	T1	71.1°C	101.6°C	29	Q100	69.9°C	100.4°C	30	Q103	70.7°C	100.9°C	31	L100	73.5°C	105.4°C	32	C115	68.1°C	99.2°C	33	LF100	58.4°C	89.4°C	34	C103	68.5°C	99.2°C	35	C102	66.3°C	96.9°C	36	U201	66.3°C	96.5°C	37	U5	65.9°C	96.0°C	38	Q204	65.8°C	95.8°C	39	Q37	69.7°C	99.0°C	40	U3	69.7°C	99.5°C	41	Q17	69.4°C	100.0°C
NO	Position	ROOM AMBIENT Ta= 25 °C	HIGH AMBIENT Ta= 55 °C																																																																																																																																																																									
1	LF1	66.6°C	96.4°C																																																																																																																																																																									
2	C17	69.7°C	98.9°C																																																																																																																																																																									
3	LF2	71.6°C	101.2°C																																																																																																																																																																									
4	Q1	66.0°C	95.4°C																																																																																																																																																																									
5	C6	68.9°C	98.4°C																																																																																																																																																																									
6	Q10	68.4°C	98.0°C																																																																																																																																																																									
7	ZNR1	61.8°C	91.2°C																																																																																																																																																																									
8	C14	67.4°C	96.5°C																																																																																																																																																																									
9	RY	67.6°C	96.6°C																																																																																																																																																																									
10	Q39	73.1°C	101.1°C																																																																																																																																																																									
11	R90	81.0°C	108.0°C																																																																																																																																																																									
12	D2	67.4°C	97.1°C																																																																																																																																																																									
13	Q23	69.5°C	99.7°C																																																																																																																																																																									
14	C18	68.2°C	97.7°C																																																																																																																																																																									
15	U2	70.5°C	99.9°C																																																																																																																																																																									
16	T3	72.6°C	103.0°C																																																																																																																																																																									
17	T5	71.5°C	101.5°C																																																																																																																																																																									
18	U4	76.7°C	106.6°C																																																																																																																																																																									
19	Q8	66.5°C	96.3°C																																																																																																																																																																									
20	TSW1	70.0°C	100.4°C																																																																																																																																																																									
21	T4	72.6°C	103.0°C																																																																																																																																																																									
22	Q19	65.6°C	96.0°C																																																																																																																																																																									
23	T6	71.6°C	102.1°C																																																																																																																																																																									
24	T2	73.9°C	104.4°C																																																																																																																																																																									
25	Q201	71.5°C	101.7°C																																																																																																																																																																									
26	Q104	70.1°C	100.1°C																																																																																																																																																																									
27	L101	75.8°C	107.6°C																																																																																																																																																																									
28	T1	71.1°C	101.6°C																																																																																																																																																																									
29	Q100	69.9°C	100.4°C																																																																																																																																																																									
30	Q103	70.7°C	100.9°C																																																																																																																																																																									
31	L100	73.5°C	105.4°C																																																																																																																																																																									
32	C115	68.1°C	99.2°C																																																																																																																																																																									
33	LF100	58.4°C	89.4°C																																																																																																																																																																									
34	C103	68.5°C	99.2°C																																																																																																																																																																									
35	C102	66.3°C	96.9°C																																																																																																																																																																									
36	U201	66.3°C	96.5°C																																																																																																																																																																									
37	U5	65.9°C	96.0°C																																																																																																																																																																									
38	Q204	65.8°C	95.8°C																																																																																																																																																																									
39	Q37	69.7°C	99.0°C																																																																																																																																																																									
40	U3	69.7°C	99.5°C																																																																																																																																																																									
41	Q17	69.4°C	100.0°C																																																																																																																																																																									





2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P : 24 VDC O/P : 130.7% LOAD Ta : 25°C	TEST : OK
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 16.8 VDC / 33.6 VDC O/P : 100 % LOAD Ta= -45 °C	TEST : OK
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 °C /95 %R.H NO DAMAGE	I/P : 35 VDC O/P : FULL LOAD Ta= 55 °C HUMIDITY= 95 %R.H	TEST : OK
5	TEMPERATURE COEFFICIENT	± 0.03%/°C (0~55°C)	I/P : 24 VDC O/P : FULL LOAD	± 0.0061%/°C (0~50°C)
6	STORAGE TEMPERATURE TEST	-40~85°C	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : STATIC	
7	THERMAL SHOCK TEST	-40~55°C	1. Thermal shock Temperature : -45°C~ +60°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 15cycle: 24 VDC / FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle: 24VDC / FULL LOAD Burn In Test	
8	VIBRATION TEST	10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10 min/sweep cycle (4) Acceleration : 6G (5) Test Time : 180min in each axis (X.Y.Z) (6) Ta : 25°C	
9	CAPACITOR LIFE CYCLE	SUPPOSE C103 IS THE MOST CRITICAL COMPONENT (1) I/P : 24VDC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 24VDC O/P : FULL LOAD Ta= 55 °C LIFE TIME (3) I/P : 24VDC O/P : 75% LOAD Ta= 55 °C LIFE TIME (4) I/P : 24VDC O/P : 50% LOAD Ta= 55 °C LIFE TIME		(1) 308214.1HRS (2) 36702.1HRS (3) 73241HRS (4) 136853.4HRS
10	MTBF	Conducted by Parts Stress Analysis Prediction 277.9K hrs min. Telcordia SR-332 (Bellcore) ; 99.1K hrs min. MIL-HDBK-217F (25°C)		
11	Ongoing Reliability Test	I/P : 24VDC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 30,000 hours		

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		Wangdz

2018.4.30 GP-A50-F010