



Test Report : SCWN03E-05

3W DIP Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	-0.30 %	P
2	RIPPLE & NOISE	50 mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	16.8 mV	P
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:4.5VDC-9VDC O/P:FULL LOAD Ta:25°C	+0.001% ~ +0.040%	P
4	LOAD REGULATION	-0.5% ~ +0.5% (Max)	I/P:5VDC O/P:10% LOAD-FULL LOAD Ta:25°C	-0.08 % ~ +0.08 %	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	78 % (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25°C	79.34 %	P
2	DC CURRENT	779 mA / FULL LOAD (Max) 15 mA / NO LOAD (Max)	I/P:5VDC O/P:NO / FULL LOAD Ta:25°C	754 mA / FULL LOAD 6 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	120%~250% LOAD (Typ)	I/P:5VDC O/P:TESTING Ta:25°C	172 %	P
2	INPUT UNDER VOLTAGE PROTECTION	POWER DOWN 4.2V (Typ) POWER UP 4.4V (Typ)	I/P:TESTING O/P: 10% LOAD Ta:25°C	POWER DOWN:3.99V POWER UP:4.12V	P
3	SHORT PROTECTION	CONTINUOUS	I/P:9VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE OK	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:3000 VDC/min	I/P-O/P:3000 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 12HRS I/P:5VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 12HRS I/P:5VDC O/P:FULL LOAD Ta=85°C	<table border="1" data-bbox="651 1055 1147 1149"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>35.7°C</td> <td>94.7°C</td> </tr> </tbody> </table>	NO	Position	1	2	1	CASE	35.7°C	94.7°C		P
NO	Position	1	2										
1	CASE	35.7°C	94.7°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:5VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.368 M.T.B.F : 2,720,404 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ALROY WANG	VINCENT ZENG