



# Test Report : SKA20B-12

---

20W DC-DC Regulated Single Output Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:24VDC O/P:100% LOAD Ta:25°C	0.57%	P
2	RIPPLE & NOISE	60mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	20mV	P
3	LINE REGULATION	-0.2%~+0.2% (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	-0.01% ~ +0.01%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:12VDC O/P:MIN-FULL LOAD Ta:25°C	-0.04% ~ +0.05%	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	15.7~36VDC	P
2	EFFICIENCY	88.5% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	88.61%	P
3	DC CURRENT	970 mA / FULL LOAD (Max) 25 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	942 mA / FULL LOAD 13 mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~180%	I/P:24VDC O/P:TESTING Ta:25°C	157.9% HICCUP MODE AUTO-RECOVER	P
2	INPUT OVER VOLTAGE PROTECTION	>40VDC~43VDC (Typ)	I/P:TESTING O/P:MINI. LOAD Ta:25°C	42.1 VDC SHUTDOWN OUTPUT VOLTAGE AUTO-RECOVER	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

## CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C > 2.5Vdc or open Power off : R.C < 0.8Vdc or short (-Vin)	I/P:24VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>1.1Vdc or Open Power off : R.C<1.08Vdc or Short	P
2	TRIM CONTROL	-20%~ +10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 20k ohm VR	I/P:24VDC O/P:FULL LOAD Ta:25°C	Trim DOWN -26.73% Trim UP +10.11%	P

## SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

## RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 5 HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 15 HRS I/P:24VDC O/P:FULL LOAD Ta=75°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>57.5°C</td> <td>102.5°C</td> </tr> </tbody> </table>				NO	Position	P/N	1	2	1	CASE	CENTER	57.5°C	102.5°C
NO	Position	P/N	1	2											
1	CASE	CENTER	57.5°C	102.5°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:24VDC O/P: 100% LOAD Ta= -40°C	TEST : OK	P										

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2011.11.15	RD SAMPLE 1122R	PASS	PETER	VINCENT